

FCC Verification TEST REPORT

Prepared For :	Zhongshan Mingzhi Lighting Co., LTD Add: 5th Floor, 146 yuca Road, Jiuzhou, Xiaolan Town, Zhongshan City, Guangdong Province, China
Product Name:	LED induction lamp(Ultra-thin bottom luminous human body)
Trade Mark	明枝 mingzhi
Model :	MZ-L1801, MZ-L1802, MZ-L1803, MZ-L1804, MZ-L1805, MZ-L1806, MZ-L1807, MZ-L1808
Prepared By :	Shenzhen SIT Testing Technology Co., Ltd. Add: Room 401, A2 Building, The 2nd industrial zone of ZhuAo, GuShu Village, XiXiang Town, BaoAn District, ShenZhen
Test Date:	May 25, 2022 to June 02, 2022
Date of Report :	June 02, 2022
Report No.:	SIT220525580201FR

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen SIT Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen SIT Testing Technology Co., Ltd, personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	3
2 EUT DESCRIPTION	3
3.TEST METHODOLOGY	5
3.1 DECISION OF FINAL TEST MODE	5
3.2 EUT SYSTEM OPERATION	5
4 SETUP OF EQUIPMENT UNDER TEST	6
4.1 DESCRIPTION OF SUPPORT UNITS	6
4.2 CONFIGURATION OF SYSTEM UNDER TEST	6
5 FACILITIES AND ACCREDITATIONS	7
5.1 FACILITIES	7
5.2 ACCREDITATIONS	7
5.3 MEASUREMENT UNCERTAINTY	7
6 CONDUCTED EMISSION MEASUREMENT	8
6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
6.2. TEST INSTRUMENTS	8
6.3 TEST PROCEDURES	9
6.4.TEST SETUP	10
6.5. TEST RESULTS	10
7 RADIATED EMISSION MEASUREMENT	11
7.1 LIMITS OF RADIATED EMISSION MEASUREMENT	11
7.2 TEST INSTRUMENTS	11
7.3 TEST PROCEDURES	12
7.4 TEST SETUP	14
7.5 TEST RESULTS	14
8 PHOTOGRAPHS OF THE TEST CONFIGURATION	17
9 PHOTOGRAPHS OF EUT	18

1 TEST RESULT CERTIFICATION

Product: LED induction lamp(Ultra-thin bottom luminous human body)

Model: MZ-L1801, MZ-L1802, MZ-L1803, MZ-L1804, MZ-L1805, MZ-L1806, MZ-L1807, MZ-L1808

Applicant: Zhongshan Mingzhi Lighting Co., LTD

Add: 5th Floor, 146 yucui Road, Jiuzhou, Xiaolan Town, Zhongshan City, Guangdong Province, China

Factory: Zhongshan Mingzhi Lighting Co., LTD

Add: 5th Floor, 146 yucui Road, Jiuzhou, Xiaolan Town, Zhongshan City, Guangdong Province, China

Trade Mark: 明枝
mingzhi


EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 ANSI C63.4-2014	Conducted (Main Port)	N/A	N/A
	Radiated	PASS	Meet Requirement

Note: 1. The test result judgment is decided by the limit of measurement standard

2. The information of measurement uncertainty is available upon the customer's request.

The above equipment has been tested by Shenzhen SIT Testing Technology Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Prepared by :



Assistant

Reviewer :



Supervisor

Approved & Authorized Signer :



2 EUT DESCRIPTION

Product	LED induction lamp(Ultra-thin bottom luminous human body)
Model	MZ-L1801
Trade Mark	明枝
Applicant	Zhongshan Mingzhi Lighting Co., LTD
Housing material	Plastic&Metal
EUT Type	☒ Engineering Sample. ☐ Product Sample, ☐ Mass Product Sample.
Serial Number	N/A
Power Rating	Input: 5V $\overline{\underline{\hspace{0.5em}}}$, 1.55W

3. TEST METHODOLOGY

3.1 DECISION OF FINAL TEST MODE

The EUT was tested together with the thereafter additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The following test mode(s) were scanned during the preliminary test:

Pre-Test Mode		
Emission	Conducted Emission	Mode: N/A
	Radiated Emission	Mode: Normal working

After the preliminary scan, the following test mode was found to produce the highest emission level.

The Worst Test Mode		
Emission	Conducted Emission	Mode: N/A
	Radiated Emission	Mode: Normal working

Then, the EUT configuration and cable configuration of the above highest emission mode was chosen for all final test items.

3.2 EUT SYSTEM OPERATION

1. Set up EUT with the relative support equipments.
2. Make sure the EUT worked normally during the test.

4 SETUP OF EQUIPMENT UNDER TEST

4.1 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Mark	Data Cable	Power Cord
N/A	/	/	/	/	/	/	/

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 CONFIGURATION OF SYSTEM UNDER TEST

EUT

(EUT: LED induction lamp(Ultra-thin bottom luminous human body))

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at **SIT LAB**.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Copies of granted accreditation certificates are available for downloading from our web site, [http:// www.sit-cert.com](http://www.sit-cert.com)

USA	FCC
	TIMCO
Germany	TUV
	EMCC
Japan	VCCI
Canada	INDUSTRY CANADA

5.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency		Uncertainty
Conducted emissions	9kHz~30MHz		+/- 3.59dB
Radiated emissions	Horizontal	30MHz ~ 200MHz	+/- 4.77dB
		200MHz ~1000MHz	+/- 4.93dB
	Vertical	30MHz ~ 200MHz	+/- 5.04dB
		200MHz ~1000MHz	+/- 4.93dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

6 CONDUCTED EMISSION MEASUREMENT

6.1. LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

6.2. TEST INSTRUMENTS

Conducted Emission Shielding Room Test Site 743				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100005	09/29/2021
LISN	AFJ	LS16	16010222119	09/29/2021
LISN	Mestec	AN3016	04/10040	09/24/2021

- NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to International system of unit (SI).
2. N.C.R = No Calibration Request.

6.3 TEST PROCEDURES

Procedure of Preliminary Test

The EUT and Support equipment, if needed, was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 9 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in Item 3.1 were scanned during the preliminary test.

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.


Procedure of Final Test

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

6.4. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

6.5. TEST RESULTS

Model No.	MZ-L1801	6dB Bandwidth	10 KHz
Environmental Conditions	26°C, 60% RH	Test Mode	Normal working
Detector Function	Peak / Quasi-peak/AV	Test Result	N/A
Test By	DebeYu		

NOTE: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

2. "---" denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.

Freq. = Emission frequency in MHz

Reading level(dBuV) = Receiver reading

Corr. Factor (dB) = Attenuator Factor+ Cable loss

Level (dBuV) = Reading level(dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Level (dBuV) – Limits (dBuV)

Q.P.=Quasi-Peak

7 RADIATED EMISSION MEASUREMENT

7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Maximum permissible level of Radiated Emission measured at 3 meter

FREQUENCY (MHz)	dBuV/m (At 3m)
	Class B
30~88	40.00
88~216	43.50
216~960	46.00
960~1000	44.00

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

7.2 TEST INSTRUMENTS

Radiated Emission Test Site 966				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	100005	09/29/2021
Pre Amplifier	H.P.	HP8447E	2945A02715	09/29/2021
Bilog Antenna	SUNOL Sciences	JB3	A021907	09/24/2021
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	09/21/2021
System-Controller	CCS	N/A	N/A	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to International system of unit (SI).

2. N.C.R = No Calibration Request.

7.3 TEST PROCEDURES

Procedure of Preliminary Test

The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

Support equipment, if needed, was placed as per ANSI C63.4.

All I/O cables were positioned to simulate typical usage as per ANSI C63.4.

Mains cables, telephone lines or other connections to auxiliary equipment located outside the test area shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No extension cords shall be used to mains receptacle.

The antenna was placed at 3 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.

The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

The test mode(s) described in Item 3.1 were scanned during the preliminary test:

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.

The EUT and worse cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

When measuring emissions above 1GHz, the frequencies of maximum emission shall be determined by manually positioning the antenna close to the EUT and by moving the antenna over all sides of the EUT while observing a spectral display. It will be advantageous to have prior knowledge of the frequencies of emissions above 1GHz. If the EUT is a device with dimensions approximately equal to that of the measurement antenna beam width, the measurement antenna shall be aligned with the EUT.

Procedure of Final Test

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.

The Analyzer / Receiver scanned from 30MHz to 1000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

For the measurement above 1GHz, use the cable, EUT arrangement, and mode of operation determined in the exploratory testing to produce the emission that has the highest amplitude relative to the limit.

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the antenna in the “cone of radiation” from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.


The antenna may have to be higher or lower than the EUT, depending on the EUT’s size and mounting height, but the antenna should be restricted to a range of height of from 1m to 4m above the ground or reference ground plane.

If the transmission line for the measurement antenna restricts its range of height and polarization, the steps needed to ensure the correct measurement of the maximum emissions, shall be described in detail in the report of the measurements.

- 1) using the procedures above to measure with peak detector function, if the result comply with the average limit specified by the appropriate regulation, record the EUT arrangement, mode of operation, and cable positions used for final radiated emission measurement , this can be done with either diagrams or photographs.
- 2) Set the detector function of the measuring instrument to average mode, using the procedures above and remeasure only those emissions that complied with the peak limits but exceeded the average limits.

Recorded at least the six highest emissions.

7.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.5 TEST RESULTS

Model No.	MZ-L1801	Test Mode	Normal working
Environmental Conditions	26°C, 60% RH	6dB Bandwidth	120 KHz
Antenna Pole	Vertical / Horizontal	Antenna Distance	3m
Detector Function	Peak / Quasi-peak	Test Result	Pass

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading


Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Job No.:	RE	Polarization:	Horizontal
Standard:	FCC Class B 3M Radiation	Power Source:	
Test item:	Radiation Test	Date:	2022/05/30
Temp.(C)/Hum.(%RH):	23.5(C)/54%RH	Time:	10:18:35
EUT:	LED induction lamp(Ultra-thin bottom luminous human body)	Test By:	
Model:	MZ-L1801	Distance:	3m



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.1616	28.27	-11.06	17.21	40.00	-22.79	peak
2	47.3255	32.44	-10.89	21.55	40.00	-18.45	peak
3	100.9339	28.42	-12.14	16.28	43.50	-27.22	peak
4	146.3735	32.48	-15.25	17.23	43.50	-26.27	peak
5	470.5232	28.46	-5.35	23.11	46.00	-22.89	peak
6	860.0352	29.13	-0.29	28.84	46.00	-17.16	peak


Job No.:	RE	Polarization:	Vertical
Standard:	FCC Class B 3M Radiation	Power Source:	
Test item:	Radiation Test	Date:	2022/05/30
Temp.(C)/Hum.(%RH):	23.5(C)/54%RH	Time:	10:17:32
EUT:	LED induction lamp(Ultra-thin bottom luminous human body)	Test By:	
Model:	MZ-L1801	Distance:	3m



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.0783	37.63	-11.25	26.38	40.00	-13.62	peak
2	46.6664	34.77	-10.89	23.88	40.00	-16.12	peak
3	103.4421	28.56	-12.27	16.29	43.50	-27.21	peak
4	182.5592	40.25	-13.71	26.54	43.50	-16.96	peak
5	208.5803	31.99	-12.14	19.85	43.50	-23.65	peak
6	645.1195	29.66	-3.37	26.29	46.00	-19.71	peak


8 PHOTOGRAPHS OF THE TEST CONFIGURATION

RADIATED EMISSION TEST




9 PHOTOGRAPHS OF EUT


Appearance photograph of EUT




Appearance photograph of EUT




Appearance photograph of EUT




Appearance photograph of EUT




Appearance photograph of EUT




Appearance photograph of EUT



Appearance photograph of EUT



Appearance photograph of EUT



-----THE END-----