



中国认可
国际互认
检测
TESTING
CNAS L4743

Test Report

No. AJFS2004003123FF

Date: MAY.08, 2020

Page 1 of 3

ANJI GONGCHUANG PROPERTY MANAGEMENT CO., LTD.

MODERN INDUSTRIAL PARK, TIANZIHU TOWN, ANJI COUNTY, ZHEJIANG PROVINCE

The following sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. results apply to the sample as received.

Sample Description: FOAM

Color: GREY

Style/Item No.: /

Test Requested:

State of California, Department of Consumer Affairs, Bureau of Electronic & Appliance Repair, Home Furnishings & Thermal Insulation, Technical Bulletin 117-2013, Requirement, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture, Section 3, Resilient Filling Material Test.

Test Results: -- See attached sheet --

Conclusion: The Submitted Sample **meets** the Requirements of Section 3 for Resilient Filling Material Test of California Technical Bulletin 117-2013.

Test Period:

Sample Receiving Date : APR.29, 2020

Test Performing Date : APR.29, 2020 TO MAY 08, 2020

Signed for and on behalf of
SGS-CSTC Co., Ltd. Anji Branch

Allen Zou
Lab Manager

scan to see the report



AJFS2004003123FF



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Anji Branch Fire Technology Service Co., Ltd.
Anji Branch Fire Technology Service

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Member of the SGS Group (SGS SA)

Test Report

No. AJFS2004003123FF

Date: MAY.08, 2020

Page 2 of 3

I. Test Conducted

This test was conducted in accordance with California Technical Bulletin 117-2013 Testing the Smolder Resistance of Materials Used in Upholstered Furniture, Section 3: Resilient Filling Material Test.

II. Details of tested specimen

Sample description / Color	Foam / Grey
Density	23.8 kg/m ³
Sample size	203mm×127mm×51mm & 203mm×203mm×51mm

III. Conditioning

Prior to testing, the specimens were conditioned for a minimum of 24 hours, at 70 ± 5°F (21°C ± 3°C) and less than 55% relative humidity.

IV. Test results

Specimen No.	Duration of smoldering (min:sec)	Open flaming (Yes/No)	Vertical char length (mm)	Comments
1	32min41s	No	17	Pass
2	31min50s	No	18	Pass
3	32min17s	No	16	Pass

PASS/FAIL CRITERIA:

1. A single mock-up test specimen fails the requirements of this test procedure if any of the following criteria occurs:
 - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
 - b) A vertical char length (measured as described in step 17.9 of ASTM E1353-08a ^{§1}) of more than 1.5 inches (38 mm) develops on the cover fabric.
 - c) The mock-up test specimen transitions to open flaming.
2. The resilient filling material passes the test if three mock-up specimens pass the test.
3. If more than one specimen fails, the resilient filling material fails the test.
4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
5. If all three additional specimens pass the test, the resilient filling material passes the test. If any one of the additional three specimens fails, the resilient filling material fails the test.

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.ssgroup.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Report

No. AJFS2004003123FF

Date: MAY.08, 2020

Page 3 of 3

STATEMENTS:

This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.

The test results only to the ignitability of the sample or combination of materials under the particular condition of test. They are not intended as a means of assessing the full potential fire hazard of the materials or products in use.

The specimen was supplied by the sponsor and SGS-CSTC ANJI Branch was not involved in any selection or sampling procedure.

Photo Appendix:



SGS authenticate the photo on original report only

End of Report