

TEST REPORT

APPLICANT : Anji Guqiang Furniture CO.,Ltd

ADDRESS : NO1.Tangpu Industrial Zone,Anji
County,Huzhou,Zhejiang,China 313300

SAMPLE DESCRIPTION : Foam

COUNTRY OF ORIGIN : China

SAMPLE RECEIVED DATE : 09-Nov-2021

TURN AROUND TIME : 09-Nov-2021 to 15-Nov-2021

The following test item(s) was/were performed on submitted sample(s) and/or component(s) confirmed by applicant

TEST REQUESTED	TEST METHOD/REGULATION	RESULT
Resilient Filling Material Test	California Technical Bulletin 117-2013 Section 3	Pass


Eurofins (Hangzhou) contact information

Customer service: StaceyZhang@eurofins.com/ +86 571 87203730

Sales specialist: SophiaMa@eurofins.com/ +86 13336882996

***** FOR FURTHER DETAILS, PLEASE REFER TO THE FOLLOWING PAGE(S) *****

Signed for and on behalf of
Eurofins Product Testing Service (Shanghai) Co., Ltd. Hangzhou Branch



Sara Liu
Lab Manager

Samples are obtained by express delivery, Results obtained refer only to samples, products or material received in Laboratory, as described in point related to sample description, and tested in conditions shown in present report. Eurofins Product Testing Service (Shanghai) Co., Ltd ensures that this job has been performed according to our Quality System and complying contract and legal conditions. If you happen to have any comments, please do it by sending email to info.hz@eurofins.com and referring to this report number. Reproduction of this document is only valid if it is done completely and under the written permission of Eurofins Product Testing Service (Shanghai) Co., Ltd. If you happen to have any complaints, please do it by sending email to chinacomplaint@eurofins.com and referring to this report number.

SAMPLE PHOTO(S)



A

EFHZ21110872-CG-01

TEST RESULT

Resilient Filling Material Test

California Technical Bulletin 117-2013 Section 3

Conditioning: Prior to testing, the specimens were conditioned for a minimum of 24 hours, at 70±5°F (21°C±3°C) and less than 55% relative humidity.

Test Result:

Sample Description: Foam

Specimen	Obvious open flaming	Vertical Char Length (nearest 0.1 inch)	Continues to smolder after the 45 minute test duration	Comment
1	No	0.6	No	Pass
2	No	0.5	No	Pass
3	No	0.6	No	Pass

Requirement:

1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs
 - a) The mock-up test specimen continues to smolder after the 45 minute test duration
 - b) A vertical char length of more than 1.5 inches(38mm) develops on the cover fabric
 - c) The mock-up test specimen transitions to open flaming
2. The resilient filling material passes the test if three mock-up specimens pass the test
3. If more than one specimen fails. The resilient filling material fails the test
4. If any one of the three initial specimens fails. Repeat the test on additional three specimens.
5. If all three additional specimens pass the test, the resilient filling material passes the test. If any one of the additional three specimens fails. The resilient filling material fails the test.

END OF THE REPORT