



Descriptive Report

MASTER CONTRACT: 303560

REPORT: 80155045

PROJECT: 80155045

Edition 1: May 31, 2023; Project 80155045 - Guangzhou

Prepared By: Sean Xia

Authorized By: Sean Xia

Contents: Certificate of Compliance - Page 1 to 2
Supplement to Certificate of Compliance - Page 1
Description and Tests - Pages 1 to 12
Att1 Figures - 1 to 7
Att2 Part 6 Plan

PRODUCTS

CLASS 2711-04 DOMESTIC GAS COOKING APPL – Outdoor

CLASS 2711-84 DOMESTIC GAS COOKING APPL – Outdoor-Certified to U.S. Standards

For use with Liquefied Petroleum Gases Open Top Broiler, Portable

Model Number	Trade Name	Input Rating
GM42020250A2-SB, GM40020250A2-SB, GM44010150A2-SB, GM24040450A2-SB, GM20050530A2-SB, GM24090730A2-SB	Kangdao	Main burner: 2@12,000 Btu/hr Side burner: 12,000 btu/hr
GM42020250A3-SB, GM40020250A3-SB, GM44010150A3-SB, GM24040450A3-SB, GM20050530A3-SB, GM24090730A3-SB	Kangdao	Main burner: 3@12,000 Btu/hr Side burner: 12,000 btu/hr
GM42020250A4-SB, GM40020250A4-SB, GM44010150A4-SB, GM24040450A4-SB, GM20050530A4-SB, GM24090730A4-SB	Kangdao	Main burner: 4@12,000 Btu/hr Side burner: 12,000 btu/hr
GM42020250A5-SB, GM40020250A5-SB, GM44010150A5-SB, GM24040450A5-SB, GM20050530A5-SB GM24090730A5-SB	Kangdao	Main burner: 5@12,000 Btu/hr Side burner: 12,000 btu/hr
GM42020250A2-DB, GM40020250A2-DB, GM44010150A2-DB, GM24040450A2-DB, GM20050530A2-DB, GM24090730A2-DB	Kangdao	Main burner: 2@12,000 Btu/hr Side burner: 8,500 btu/hr
GM42020250A3-DB, GM40020250A3-DB, GM44010150A3-DB, GM24040450A3-DB, GM20050530A3-DB, GM24090730A3-DB	Kangdao	Main burner: 3@12,000 Btu/hr Side burner: 8,500 btu/hr
GM42020250A4-DB, GM40020250A4-DB, GM44010150A4-DB, GM24040450A4-DB, GM20050530A4-DB, GM24090730A4-DB	Kangdao	Main burner: 4@12,000 Btu/hr Side burner: 8,500 btu/hr

The reader is responsible for any liability arising from actions taken in interpreting or applying the results presented in this report. This report shall not be reproduced except in full, without written approval from CSA Group Testing & Certification Inc. The results of this report only relate to those items tested.

No. 10, Ke Yan Road, Guangzhou Science Park, Luo Gang District, Guangzhou, 510663, China
Telephone: (86)20.87320648 Fax: (86)20.87320306 www.csagroup.org

GM42020250A5-DB, GM40020250A5-DB, GM44010150A5-DB, GM24040450A5-DB, GM20050530A5-DB GM24090730A5-DB	Kangdao	Main burner: 5@12,000 Btu/hr Side burner: 8,500 btu/hr
GM42020250A2, GM40020250A2, GM44010150A2, GM24040450A2, GM20050530A2, GM24090730A2	Kangdao	Main burner: 2@12,000 Btu/hr
GM42020250A3, GM40020250A3, GM44010150A3, GM24040450A3, GM20050530A3, GM24090730A3	Kangdao	Main burner: 3@12,000 Btu/hr
GM42020250A4, GM40020250A4, GM44010150A4, GM24040450A4, GM20050530A4, GM24090730A4	Kangdao	Main burner: 4@12,000 Btu/hr
GM42020250A5, GM40020250A5, GM44010150A5, GM24040450A5, GM20050530A5, GM24090730A5	Kangdao	Main burner: 5@12,000 Btu/hr
GS03070711B2-SB, GS07070710B2-SB	Kangdao	Main burner: 2@10,000 Btu/hr Side burner: 8,500 btu/hr
GS03070711B3-SB, GS07070710B3-SB	Kangdao	Main burner: 3@10,000 Btu/hr Side burner: 8,500 btu/hr
GS03070711B4-SB, GS07070710B4-SB	Kangdao	Main burner: 4@10,000 Btu/hr Side burner: 8,500 btu/hr
GS03070711B2-DB, GS07070710B2-DB	Kangdao	Main burner: 2@10,000 Btu/hr Side burner: 12,000 btu/hr
GS03070711B3-DB, GS07070710B3-DB	Kangdao	Main burner: 3@10,000 Btu/hr Side burner: 12,000 btu/hr
GS03070711B4-DB, GS07070710B4-DB	Kangdao	Main burner: 4@10,000 Btu/hr Side burner: 12,000 btu/hr
GS03070711B2, GS07070710B2	Kangdao	Main burner: 2@10,000 Btu/hr
GS03070711B3, GS07070710B3	Kangdao	Main burner: 3@10,000 Btu/hr
GS03070711B4, GS07070710B4	Kangdao	Main burner: 4@10,000 Btu/hr

APPLICABLE REQUIREMENTS

ANSI Z21.58-2018 / CSA 1.6-2018 Outdoor Cooking Gas Appliances

MARKINGS

The manufacturer is required to apply the following markings:

- Products shall be marked with the markings specified by the particular product standard.
- Products certified for Canada shall have all Caution and Warning markings in both English and French.

Additional bilingual markings not covered by the product standard(s) may be required by the Authorities Having Jurisdiction. It is the responsibility of the manufacturer to provide and apply these additional markings, where applicable, in accordance with the requirements of those authorities.

The products listed are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US (indicating that products have been manufactured to the requirements of both Canadian and U.S. Standards) or with adjacent indicator 'US' for US only or without either indicator for Canada only.

All markings are in compliance with the above-mentioned requirements. Samples are contained in the main certification report in figures #12.

ALTERATIONS

Project 80155045

- Ø Changed location of bar in the cylinder enclosure to avoid spare cylinder stored. See Figure #3-43, 64.
- Ø Add lighting rod. See Figure #1-68.
- Ø Change hole size of shield near ignition pin to pass rain test. See Figure #1-132.
- Ø Change lid angle, add depth of burner pot, change injection part of burner for GS-SB series to pass the win test. See Figure #1-18, 1-19, 3-24.
- Ø Change lid angle, add depth of burner pot for GM-SB series to pass the wind test. See Figure ##1-18, 1-19.
- Ø Change glass lid to iron lid due to failure to glass thermal shock test.
- Ø Manual and marking altered.

FACTORY TESTS

Factory tests to be in accordance with Part 6 of the applicable requirements detailed in the Certificate of Compliance.

The submitter shall ensure that the following factory tests are conducted at the frequency specified and the results are documented and made available for review by CSA field services representatives.

<u>Test</u>	<u>Frequency</u>
Test Fire Burner, Manifold & Control Assy. - Proper Operation Pass/Fail Criteria: Valve shall turn freely The burner flames shall carryover and burn at all ports	100%
Manifold and Control Assembly - Gas Tightness Pass/Fail Criteria: No leakage shall be observed	100%
Burner Operating Characteristics Pass/Fail Criteria: The burner shall light without delay The burner flames shall carryover and burn at all ports Flames shall not flash outside the enclosure The burner shall not flash back Ignition and extinction shall occur without undue noise There shall be no backpressure at the burner mixer face	1 per 100, but no less than 1 per week
Combustion Pass/Fail Criteria: Air free CO shall not exceed 800 ppm	1 per 100, but no less than 1 per week

SPECIAL INSTRUCTIONS FOR FIELD SERVICES

1. Component descriptions marked with either the "(INT)" or "(INT*)" identifiers may be substituted with other components providing the requirements specified under the notes in the "Description" are complied with.
2. Not applicable.

COMPONENT SPECIAL PICKUP

1. Component descriptions marked with the identifier "(CT)" are subject to annual pickup and Conformity Testing.
2. Not applicable.

DESCRIPTION

Notes:

1. Component Substitution
 - a) Critical components (those identified by mfr name, cat no), which are NOT identified with either "INT" or "INT*" are not eligible for substitution without evaluation and report updating
 - b) The term "INT" means a "Certified" and/or "Listed" (or a "Recognized" and/or "Accepted") component may be replaced by one "Certified" and/or "Listed" by another certification organization accredited by the appropriate accreditation body or scheme requirements to the correct standard, for the same application; providing the applicable country identifiers are included and requirements in item "d" below are complied with.
 - c) The Term "(INT*)" means a "Recognized" and/or "Accepted" component may be replaced by a component that is CSA Certified. The applicable country identifiers shall be included, the requirements in item "d" below as well as any "conditions of suitability" for the component (as recorded in this descriptive report) shall be complied with;
 - d) Components which have been substituted, must be of an equivalent rating, configuration (size, orientation, mounting) and the applicable minimum creepage and clearance distances are to be maintained from live parts to bonded metal parts and secondary parts.
 - e) Substitution of a "Certified" and/or "Listed" component with a component that is "Recognized" or "Accepted" is not permitted without evaluation and report updating.
 - f) Substitution of a "Recognized" and/or "Accepted" component by one that is not CSA Certified is not permitted without a proper evaluation as well as a report update because the Conditions of Acceptance of the original component may be different than the Conditions of Acceptance of the substitute component.

The Outdoor Cooking Gas Appliance noted in the PRODUCTS Section of this report is designed for outdoor use with standard 20 lb propane tanks. The Outdoor Cooking Gas Appliance has a potable cart, stainless steel tube burner. The LP tank is mounted and secured inside the cart.

Refer to main report for descriptive drawings.

MODEL NUMBER BREAKDOWN

Model No.	Designation
GM42020250A2-SB	The grill with two tube main burners with input rate 12,000 Btu/hr each and one side burner with input rate 12,000 Btu/hr. For use with 20 lb LP gas cylinder.
GM42020250A3-SB	Same as model GM42020250A2-SB except with three tube main burners.
GM42020250A4-SB	Same as model GM42020250A2-SB except with four tube main burners.
GM42020250A5-SB	Same as model GM42020250A2-SB except with five tube main burners.
GM40020250A2/3/4/5-SB	Same as models GM42020250A2/3/4/5-SB except shape of lid.
GM44010150A2/3/4/5-SB	Same as models GM42020250A2/3/4/5-SB except shape of lid, control panel, side table.
GM24040450A2/3/4/5-SB	Same as models GM42020250A2/3/4/5-SB except shape of lid, control panel, side table.
GM20050530A2/3/4/5-SB	Same as models GM42020250A2/3/4/5-SB except shape of lid, control panel, side table, cylinder enclosure.
GM24090730A2/3/4/5-SB	Same as models GM42020250A2/3/4/5-SB except shape of lid, control panel, side table, cylinder enclosure.
GS03070711B2-SB	The grill with two tube main burners with input rate 10,000 Btu/hr each and one side burner with input rate 8,500 Btu/hr. For use with 20 lb LP gas cylinder.
GS03070711B3-SB	Same as model GS03070711B2-SB except with three tube main burners.
GS03070711B4-SB	Same as model GS03070711B2-SB except with four tube main burners.

GS07070710B2/3/4-SB	Same as models GS03070711B2/3/4-SB except control panel, cylinder enclosure.
GM42020250A2/3/4/5	Same as models GM42020250A2/3/4/5-SB except without side burner.
GM40020250A2/3/4/5	Same as models GM40020250A2/3/4/5-SB except without side burner.
GM44010150A2/3/4/5	Same as models GM44010150A2/3/4/5-SB except without side burner.
GM24040450A2/3/4/5	Same as models GM24040450A2/3/4/5-SB except without side burner.
GM20050530A2/3/4/5	Same as models GM20050530A2/3/4/5-SB except without side burner.
GM24090730A2/3/4/5	Same as models GM24090730A2/3/4/5-SB except without side burner.
GS03070711B2/3/4	Same as models GS03070711B2/3/4-SB except without side burner.
GS07070710B2/3/4	Same as models GS07070710B2/3/4-SB except without side burner.
GM42020250A2/3/4/5-DB	Same as models GM42020250A2/3/4/5-DB except using side burner of model GS03070711B2-SB.
GM40020250A2/3/4/5-DB	Same as models GM40020250A2/3/4/5-DB except using side burner of model GS03070711B2-SB.
GM44010150A2/3/4/5-DB	Same as models GM44010150A2/3/4/5-DB except using side burner of model GS03070711B2-SB.
GM24040450A2/3/4/5-DB	Same as models GM24040450A2/3/4/5-DB except using side burner of model GS03070711B2-SB.
GM20050530A2/3/4/5-DB	Same as models GM20050530A2/3/4/5-DB except using side burner of model GS03070711B2-SB.
GM24090730A2/3/4/5-DB	Same as models GM24090730A2/3/4/5-DB except using side burner of model GS03070711B2-SB.
GS03070711B2/3/4-DB	Same as models GS03070711B2/3/4-SB except using side burner of model GM42020250A2-SB.
GS07070710B2/3/4-DB	Same as models GS07070710B2/3/4-SB except using side burner of model GM42020250A2-SB.

INSTALLATION CLEARANCES

Side	36 inches
Rear	36 inches
Top	Not be used under overhead combustible construction
Floor	Non-Combustible

GAS PRESSURES

For Liquefied Petroleum Gas

Tested for a supply pressure of 11.0 in. W.C. (Regulated by LP regulator only)

Self Contained LP System uses a 20 lb LP cylinder constructed and marked in accordance with specifications of U.S. Department of Transportation (DOT).

Orifice Sizes

Model		Propane	Low flow orifice size
GM42020250A2/3/4/5-SB, GM40020250A2/3/4/5-SB, GM44010150A2/3/4/5-SB, GM24040450A2/3/4/5-SB, GM20050530A2/3/4/5-SB, GM24090730A2/3/4/5-SB	Main:	1.02 mm	0.67mm
	Side:	1.02 mm	0.67mm
GS03070711B2/3/4-SB, GS07070710B2/3/4-SB	Main:	0.93 mm	0.67mm
	Side:	0.86 mm	0.67mm

GM42020250A2/3/4/5, GM40020250A2/3/4/5, GM44010150A2/3/4/5, Main: 1.02 mm 0.67mm
 GM24040450A2/3/4/5, GM20050530A2/3/4/5, GM24090730A2/3/4/5

GS03070711B2/3/4, GS07070710B2/3/4 Main: 0.93 mm 0.67mm

GM42020250A2/3/4/5-DB, GM40020250A2/3/4/5-DB, Main: 1.02 mm 0.67mm
 GM44010150A2/3/4/5-DB, GM24040450A2/3/4/5-DB, Side: 0.86 mm 0.67mm
 GM20050530A2/3/4/5-DB, GM24090730A2/3/4/5-DB

GS03070711B2/3/4-DB, GS07070710B2/3/4-DB Main: 0.93 mm 0.67mm
 Side: 1.02 mm 0.67mm

Gas Control Assemblies

Read columns vertically
 for complete assemblies

For all models

TYPE OF CONTROL	MFR OF CONTROL	MFR MODEL NUMBER	NATURAL	LP/PROPANE
Gas Valves Main burner	Ningbo Chaoyang	CD001C01, CD301C01 (CSA 1426412)	-	X
	Zhongshan Leetron	A100-1, A130-0 (CSA 1769699)	-	X
	Guangdong KSUN	B500, B530 (CSA 2727123)	-	X
Ignitor pin	Yangzhou Minghui	MH-0115-A (CSA 2444646)		X
Wire	Jiangsu Naian	1015 (UL E217633)		X
Corrugated pipe	Hefei Huimeite	HMTB-1 (CSA 2385151)		X
	Shanghai Laineng	100-1014-L (CSA 1675450)		X
Marking Material	Zhongshan Zhantu	ZT-2 (CSA 70132823)	-	X
Hose Assembly (Type of cylinder connector: QCC, Angle between QCC and regulator 0 degree, Length of hose assembly=300mm, 5/16")				
	Ningbo Laite	JY70A11A, JY95A6A (CSA 2055064)	-	X
	Guangdong KSUN	RYQB01 (CSA 2431817)	-	X
For models GM42020250A2/3/4/5-SB, GM40020250A2/3/4/5-SB, GM44010150A2/3/4/5-SB, GM24040450A2/3/4/5-SB, GM20050530A2/3/4/5-SB, GM24090730A2/3/4/5-SB, GS03070711B2/3/4-SB, GS07070710B2/3/4-SB, GM42020250A2/3/4/5-DB, GM40020250A2/3/4/5-DB, GM44010150A2/3/4/5-DB, GM24040450A2/3/4/5-DB, GM20050530A2/3/4/5-DB, GM24090730A2/3/4/5-DB, GS03070711B2/3/4-DB, GS07070710B2/3/4-DB				

MASTER CONTRACT: 303560

REPORT: 80155045

PROJECT: 80155045

Page No: 8

Date Issued: May 31, 2023

Gas Valves Side burner	Guangdong KSUN	B400S (CSA 2727123)	-	X
---------------------------	-------------------	---------------------	---	---

DRAWING INDEX

**PAGE NO. OR
FIGURE NO.**

DESCRIPTION

Project 80155045

1	Drawings GM42020250A2/3/4/5-SB/DB
2	Drawings GM40020250A2/3/4/5-SB/DB, GM44010150A2/3/4/5-SB/DB, GM24040450A2/3/4/5-SB/DB, GM20050530A2/3/4/5-SB/DB, GM24090730A2/3/4/5-SB/DB
3	Drawings GS03070711B2/3/4-SB/DB, GS07070710B2/3/4-SB/DB
4	Drawings GM42020250A2/3/4/5, GM40020250A2/3/4/5, GM44010150A2/3/4/5, GM24040450A2/3/4/5, GM20050530A2/3/4/5, GM24090730A2/3/4/5, GS03070711B2/3/4, GS07070710B2/3/4
5	Manual GM42020250A2-SB, GM42020250A2
6	Marking GM42020250A2/3/4/5-SB, GM42020250A2/3/4/5
7	Guarantee Letter
Att2	Part 6 Plan

TEST HISTORY

Project 80155045

The following tests were conducted in:
CSA CPE Shanghai
1st Floor, Building 4, Qilai Industrial City,
889 Yishan Road, Shanghai, 200233
China

ANSI Z21.58-2018/CSA 1.6-2018 Outdoor Cooking Gas Appliances

Original certificate of models GM42020250A2/3/4/5, GM40020250A2/3/4/5, GM44010150A2/3/4/5, GM24040450A2/3/4/5, GM20050530A2/3/4/5, GM24090730A2/3/4/5, GS03070711B2/3/4, GS07070710B2/3/4, GM42020250A2/3/4/5-SB, GM40020250A2/3/4/5-SB, GM44010150A2/3/4/5-SB, GM24040450A2/3/4/5-SB, GM20050530A2/3/4/5-SB, GM24090730A2/3/4/5-SB, GS03070711B2/3/4-SB, GS07070710B2/3/4-SB, GM42020250A2/3/4/5-DB, GM40020250A2/3/4/5-DB, GM44010150A2/3/4/5-DB, GM24040450A2/3/4/5-DB, GM20050530A2/3/4/5-DB, GM24090730A2/3/4/5-DB, GS03070711B2/3/4-DB, GS07070710B2/3/4-DB.

Models GM42020250A2/3/4/5-SB series are grills have tube main burners with input rate 12,000 Btu/hr each and one side burner with input rate 12,000 Btu/hr for use with 20 lb LP gas cylinder. Tests were conducted on model GM42020250A2-SB which has two main burners and GM42020250A5-SB which has 5 main burners. Other models in this series were extended from models GM42020250A5-SB.

Models GM40020250A2/3/4/5-SB is same as models GM42020250A2/3/4/5-SB except shape of lid. Tests were conducted on model GM40020250A5-SB, other models were extended from models GM42020250A2/3/4/5-SB and GM40020250A5-SB.

Models GM44010150A2/3/4/5-SB is same as models GM42020250A2/3/4/5-SB except shape of lid, control panel, side table. Tests were conducted on model GM44010150A5-SB, other models were extended from models GM42020250A2/3/4/5-SB and GM44010150A5-SB.

Models GM24040450A2/3/4/5-SB is same as models GM44010150A2/3/4/5-SB except shape of lid which is same as models GM24090730A2/3/4/5-SB. Tests were extended from models GM44010150A2/3/4/5-SB and GM24090730A2/3/4/5-SB series..

Models GM20050530A2/3/4/5-SB is same as models GM42020250A2/3/4/5-SB except shape of lid, control panel, side table, cylinder enclosure. Tests were conducted on model GM20050530A5-SB, other models were extended from models GM42020250A2/3/4/5-SB and GM20050530A5-SB.

Models GM24090730A2/3/4/5-SB is same as models GM42020250A2/3/4/5-SB except shape of lid, control panel, side table, cylinder enclosure. Tests were conducted on model GM24090730A5-SB, other models were extended from models GM42020250A2/3/4/5-SB and GM24090730A5-SB.

Models GS03070711B2/3/4-SB series are grills have tube main burners with input rate 10,000 Btu/hr each which is same as the main burner of models GM40020250A2/3/4/5-SB except lower input rate and one side burner with input rate 8,500 Btu/hr for use with 20 lb LP gas cylinder. Tests were conducted on model GS03070711B4-SB which has four main burners. Other models in this series were extended from model GS03070711B4-SB.

Models GS07070710B2/3/4-SB is same as models GS03070711B2/3/4-SB except control panel, cylinder enclosure. Tests were conducted on model GS07070710B4-SB, other models were extended from models GS03070711B2/3/4-SB and GS07070710B4-SB.

Models GM42020250A2/3/4/5, GM40020250A2/3/4/5, GM44010150A2/3/4/5, GM24040450A2/3/4/5, GM20050530A2/3/4/5, GM24090730A2/3/4/5, GS03070711B2/3/4, GS07070710B2/3/4 are same as models GM42020250A2/3/4/5-SB, GM40020250A2/3/4/5-SB, GM44010150A2/3/4/5-SB, GM24040450A2/3/4/5-SB, GM20050530A2/3/4/5-SB, GM24090730A2/3/4/5-SB, GS03070711B2/3/4-SB, GS07070710B2/3/4-SB except without side burner. Tests were extended from models with side burner.

Model GM-DB series is same as model GM-SB series except using the side burner on model GS-SB series. Tests of GM-DB series were extended from models GM-SB and GS-SB series.

Model GS-DB series is same as model GS-SB series except using the side burner on model GM-SB series. Tests were conducted on model GS03070711B4-DB which has higher input rate than GS03070711B4-SB due to the input rate of side burner of GM-SB is higher than GS-SB. Other tests of GS-DB series were extended from models GS-SB and GM-SB series.

Tests were conducted on models GM42020250A2-SB, GM42020250A5-SB, GM40020250A5-SB, GM44010150A5-SB, GM20050530A5-SB, GM24090730A5-SB, GS03070711B4-SB, GS07070710B4-SB, GS03070711B4-DB satisfactory results were obtained and test data for this project is stored in Sharepoint:

Models GM42020250A5-SB

Clause 4 Construction

Clause 5 Performance

- 5.1 General
- 5.2 Test Gases
- 5.3 Test Pressures and Burner Adjustments
- 5.4 Burner Capacities
- 5.5 Combustion
- 5.6 Burner Operating Characteristics
- 5.7 Main Burner Placement and Integrity
- 5.8 Ignition
- 5.9 Performance of LP-Gas Cylinder Connection Devices
- 5.10 Manual Gas Valves - Waived – Used The Certified Type
- 5.11 Automatic Valves -Not applicable - None
- 5.12 Gas Pressure Regulators -Not applicable - None
- 5.13 Thermostats - Not applicable – None
- 5.14 Dual Cylinder Manifold - Not applicable
- 5.15 Orifice and Orifice Fittings
- 5.16 Temperatures of Gas-Carrying Components
- 5.17 Drip Tray Temperature
- 5.18 Broiler Performance
- 5.19 Outdoor Cooking Gas Appliance Structure
- 5.20 Evaluation of burner hazard potential of exterior surfaces of oven section – Not applicable – Not oven
- 5.21 Temperatures of handles and knobs
- 5.22 Wall and floor Temperatures
- 5.23 Rain Test
- 5.24 Nonmetallic Panels – Not applicable – No nonmetallic panel
- 5.25 Wind Tests
- 5.26 Marking Material Adhesion and Legibility Waived - Certified marking material

Clause 6 Manufacturing And Production Tests

Models GM42020250A2-SB

Clause 5 Performance

- 5.1 General
- 5.2 Test Gases
- 5.3 Test Pressures and Burner Adjustments
- 5.4 Burner Capacities

Other tests were extended from model GM42020250A5-SB

Models GS03070711B4-SB

- 5.1 General

5.2 Test Gases
5.3 Test Pressures and Burner Adjustments
5.4 Burner Capacities
5.5 Combustion
5.6 Burner Operating Characteristics
5.8 Ignition
5.19 Outdoor Cooking Gas Appliance Structure - Tip test only
5.23 Rain Test
5.25 Wind Tests
Other tests were extended from model GM42020250A5-SB.

Models GM20050530A5-SB

Clause 5 Performance

5.1 General
5.2 Test Gases
5.3 Test Pressures and Burner Adjustments
5.4 Burner Capacities
5.5 Combustion
5.19 Outdoor Cooking Gas Appliance Structure - Tip test only
5.20 Temperatures of handles and knobs
5.25 Wind Tests
Other tests were extended from model GM42020250A5-SB, GS03070711B4-SB

Models GM40020250A5-SB, GM44010150A5-SB, GM24090730A5-SB, GS07070710B4-SB

Clause 5 Performance

5.6 General
5.7 Test Gases
5.8 Test Pressures and Burner Adjustments
5.9 Burner Capacities
5.10 Combustion
5.21 Outdoor Cooking Gas Appliance Structure - Tip test only
5.26 Wind Tests
Other tests were extended from model GM42020250A5-SB, GS03070711B4-SB

Model GS03070711B4-DB

5.1 General
5.2 Test Gases
5.3 Test Pressures and Burner Adjustments
5.4 Burner Capacities
5.21 Temperatures of handles and knobs

Construction Review:

Construction review performed with satisfactory results

---End of Report---